

# Chevrolet Lighting Program



Certified Program Lighting Equipment

## Product Specifications

### HOUSING.

Die-formed steel housing assembly and reflector. Wiring access plate is provided on back of housing, for flexible conduit attachment.

### REFLECTORS.

Die-formed steel with high-reflectance white finish.

### LAMPING.

Two-lamp T5 cross-section.

### LAMP SHIELDING.


Perforated steel, 0.078" diameter holes in a staggered pattern on 0.11" centers, 46% open. Provided with white translucent overlay to shield direct view to lamps.

### BALLAST.

Low-profile, electronic, high power factor, thermally protected Class P, Sound Rated A, manufactured by a UL Listed manufacturer, as available, determined by Litecontrol. Ballasts with a voltage range of 120 to 277 will be used when fixture configuration and ballast availability allow. The minimum number of ballasts will be used.

### WARRANTY.

Special Chevrolet Lighting Program warranty, contact Wiedenbach Brown for details.

**CERTIFICATION.** Fixture and electrical components shall be UL and/or CUL Listed. 


Note: Litecontrol reserves the right to change specifications without notice for product development and improvement.

## Installation

### MOUNTING.

The fixture is intended for installation in 2' x 4' standard exposed inverted T-bar grid ceiling (NEMA type **G**). Holes provided for wire of chain mounting support to building structure.

## Dimensions



2x4